

IKONNI

Clay Collection

Standard Thickness - 3/4" , 7/8"
Max size - 4'x9'
Handles options upon request

Clay panels/doors are customized according to the customer design.

Handles options upon request.

Lead time- 6 weeks production + shipping.

IKONNI INC.

p 917-900-7048

e. info@ikonni.com

6 w 20th street, New York, NY 10011

w. ikonni.com



Solid and resistant material, makes every single product unique and Aesthetic. The clay process is purely manual. First, a primer is applied on the MDF support, followed by laying the first coat of clay, then sanding, and finally the second layer of clay. The product is finished with a final sanding, followed by varnishing, using an anti-stain acrylic surface treatment.


Standard colors



Chocolate



Country



Brick



Dust



Champeign



Stone



Lava



Mud



Irovy



Light grey



Mustard



Slat



Pitch



Marc



Sand



Snow

SPECS

The clay coatings are created with an application cycle involving several steps to be completed manually. All the application systems are developed, produced, made, and controlled in-house.

The "Top" application cycle is tested and certified

- High resistance to impacts, abrasion, and chemicals.
- Practically zero absorption of liquids.
- High compressive and flexural strength.
- Easy maintenance
- Excellent dimensional stability and lightfastness over time.

MAINTENANCE

The surface is characterized by a high degree of compactness and minimal superficial porosity. The surface treatment applied to the product makes it water-repellent, stain-proof, and resistant to the absorption of liquids, odors, and food fat. Being non-porous, the product is not subject to bacteria proliferation and is easy to clean, making it hygienic. It can withstand household and usage stains, light streaks, scratches, and minor impacts.

Protect the surface and edges against any accidental falling of blunt objects on the surface (e.g. knives, bottles, pots, work tools, etc.) as this may cause chips that may be hard or impossible to remove. To restore the surfaces, we recommend using the Touch-Up Kit specially created for restoring our surfaces. Although the material withstands high temperatures, we recommend using trivet mats to prevent direct contact with pots or crockery that have just been removed from the flame. Do not expose the material to direct flames and be careful when positioning pots on the hob, especially when backsplashes or upstands are installed. Direct contact with hot objects or flames could cause indelible stains due to heating of the surface treatment. • Avoid vigorously knocking the product with heavy objects to prevent chipping. • Do not directly cut on the surface but always use suitable support instead. • Do not use the surface as a base for ironing.

CLEANING TIPS

For daily cleaning, use a soft cloth dampened with water and mild multi-purpose neutral detergents, then dry the surface with kitchen paper.

Avoid cleaning the surface with products containing bleach, as they may leave whitish marks in case of prolonged application.

Avoid cleaning the surfaces with abrasive sponges and do not leave the surfaces in contact with steel wool or other metal objects that can contain or release oxidized particles.

Do not leave food residues to settle on the surfaces.

The surface can be stained by boiling oil residues that are not immediately removed.

The surface can also be stained by oil, coffee, lemon, red wine, and vinegar that are not removed within a few hours or within the time specified on the technical sheet.

- ✓ Customized
- ✓ Finished panel, edged, finished all sides.
- ✓ Applications
kitchen
doors/drawers
furniture
shelves
countertop
Floors
- ✓ Environment
Indoor / Outdoor
- ✓ Maintenance level
easy
- ✓ Moisture resistant

IKONNI

www.ikonni.com
info@ikonni.com